

1510nm High Power 3-port Polarization Insensitive Optical Circulator

1510nm High Power 3-port Polarization Insensitive Optical Circulator is a fiber passive component built with faraday crystal, which can change signal light transmission path, the signal can be delivered from Port 1 to Port 2, the other signal light from Port 2 to Port 3, the high isolation can block the back reflection light. It's widely used in Fiber Amplifier System, Fiber Optic Sensor and Testing System field. The handling power can be up to 30W CW.

Application:

Fiber Optic Sensor
Fiber Optic Amplifier
Coherent Detecting
Testing System

Features:

High Power
High Isolation
Low Insertion Loss
High Reliability




Specification:

Parameter	Symbol	Value	Unit
Center Wavelength	λ	1510	nm
Bandwidth	BW	± 30	nm
Typ. Insertion Loss (Port 1 to 2, 2 to 3)	IL	0.8	dB
Max. Insertion Loss (Port 1 to 2, 2 to 3)	IL	1.0	dB
Typ. Isolation (Port 2 to 1, 3 to 2)	Iso	45	dB
Min. Isolation (Port 2 to 1, 3 to 2)	Iso	35	dB
Max. Polarization Dependent Loss	PDL	0.15	dB
Max. Polarization Mode Dispersion	PMD	0.1	ps
Min. Cross Talk	Ct	50	dB
Min. Directivity		50	dB
Min. Return Loss	RL	50	dB
Max. Optical Power (CW)	P	1, 3, 5, 10, 15, 20, 30 or customized	W
Max. Peak Power	P	5, 10, 20 or customized	kW
Max. Tensile Load		5	N
Fiber Type		SMF-28e, SM-GDF-1550, 12/130DC, 14/125DC, 25/300DC fiber	-
Operating Temperature	T	-5~70	°C
Storage Temperature	T	-40~85	°C
Package Dimension		$\Phi 5.5 \times L50$ or $L90 \times W12 \times H10$	mm

Notice: Above specifications are tested at center wavelength without connector in room temperature @23°C.

For devices with connectors, IL will be 0.3dB higher, RL will be 5dB lower. connectors only 1W CW optical power guarantee.

Drawing:



Ordering Information (Part Number):

HPICIR-**WWW**-**P**-**HH**-**FF**-**J**-**LL**-**CC**

WWW	P	HH	FF	J	LL	CC
Wavelength	Port	Handling Power	Fiber Type	Fiber Jacket	Fiber Length	Connector
1510 - 1510nm	3 - 3 Ports	01 - 1W	S2 - SMF-28e	B - 250um Bare Fiber	05 - 0.5m	NE - None
1530 - 1530nm		03 - 3W	D1 - SM-GDF-1550	9 - 900um Loose Tube	10 - 1.0m	FA - FC/APC
1550 - 1550nm		05 - 5W	D2 - 12/130 DC	2 - 2.0mm Loose Tube	15 - 1.5m	FU - FC/UPC
1560 - 1560nm		10 - 10W	D3 - 14/125 DC	3 - 3.0mm Loose Tube	20 - 2.0m	SA - SC/APC
1570 - 1570nm		20 - 20W	S4 - 14/125 SC		SS - Specify	
1580 - 1580nm		30 - 30W	D5 - 25/300 DC			
SSSS - Specify		SS - Specify	SS - Specify			