

410nm 3-port Polarization Insensitive Optical Circulator

410nm 3-port Polarization Insensitive Optical Circulator is a fiber passive component built with TGG crystal, which can change signal light transmission path, the signal can be delivered from Port 1 to Port 2, the other signal light from Port 2 to Port 3, the high isolation can block the back reflection light. It's widely used in Quantum Communication, Fiber Laser and Coherent Detecting field. If need higher power version please tell us to confirm.

Application:

Quantum Communication
Fiber Laser
Coherent Detecting
Lab&Research

Features:

Low PDL
High Isolation
Low Insertion Loss
High Reliability




Specification:

Parameter	Symbol	Value	Unit
Center Wavelength	λ	410	nm
Bandwidth	BW	± 5	nm
Typ. Insertion Loss (Port 1 to 2, 2 to 3)	IL	1.5	dB
Max. Insertion Loss (Port 1 to 2, 2 to 3)	IL	1.8	dB
Typ. Isolation (Port 2 to 1, 3 to 2)	Iso	25	dB
Min. Isolation (Port 2 to 1, 3 to 2)	Iso	20	dB
Max. Polarization Dependent Loss	PDL	0.15	dB
Min. Cross Talk	Ct	45	dB
Min. Return Loss	RL	45	dB
Max. Optical Power (CW)	P	300 or customized	mW
Max. Tensile Load		5	N
Fiber Type		Nufern 405-HP fiber	-
Operating Temperature	T	+10~50	℃
Storage Temperature	T	-40-85	℃
Package Dimension			mm

Notice: Above specifications are tested at center wavelength without connector in room temperature @23℃.

For devices with connectors, IL will be 0.3dB higher, RL will be 5dB lower.

Drawing:



Ordering Information (Part Number):

PICIR-**WWW-P-J-LL-CC**

WWW	P	J	LL	CC
Wavelength	Port	Fiber Jacket	Fiber Length	Connector
405 - 405nm	3 - 3 Ports	B - 250um Bare Fiber	05 - 0.5m	NE - None
410 - 410nm		9 - 900um Loose Tube	10 - 1.0m	FA - FC/APC
420 - 420nm		2 - 2mm Loose Tube	15 - 1.5m	FU - FC/UPC
430 - 430nm		3 - 3mm Loose Tube	20 - 2.0m	SS - Specify
440 - 440nm			SS - Specify	
450 - 450nm				
458 - 458nm				
SSS - Specify				