

458nm Polarization Beam Combiner/Splitter


458nm Polarization Beam Combiner/Splitter is a fiber passive component which can combine the two orthogonal polarization light into one output fiber or split the orthogonal polarization light to two output fiber, it's widely used in Quantum Communication System and Fiber Optic Diffraction field, the high power type is available upon request.

Application:

Quantum Communication
Fiber Optic Sensor
Laser System
Fiber Optic Diffraction

Features:

High Extinction Ratio
Low Insertion Loss
Optical Path Reversibility
High Reliability




Specification:

Parameter	Symbol	Value	Unit
Center Wavelength	λ	458	nm
Bandwidth	BW	± 10	nm
Typ. Insertion Loss	IL	1.2	dB
Max. Insertion Loss	IL	1.5	dB
Min. Extinction Ratio (For PBS)	ER	20	dB
Min. Directivity		50	dB
Min. Return Loss	RL	50	dB
Max. Optical Power (CW)	P	300	mW
Max. Tensile Load		5	N
Fiber Type	For Port 1 and Port 2	PM-S405-XP fiber	-
	For Port 3	PM-S405-XP fiber or SM 405-HP fiber	-
Operating Temperature	T	-5~70	°C
Storage Temperature	T	-40~85	°C
Package Dimension			mm

Notice: Above specifications are tested at center wavelength without connector in room temperature @23 °C.

For devices with connectors, IL will be 0.3dB higher, RL will be 5dB lower, ER will be 2dB lower, slow axis is default aligned to the connector key.

Drawing:



Ordering Information (Part Number):

PBCS- WWW - FF - J - LL - CC				
WWW	FF	J	LL	CC
Wavelength	Fiber Type on Port 3	Fiber Jacket	Fiber Length	Connector
405 - 405nm	4H - 405-HP Fiber	B - 250um Bare Fiber	05 - 0.5m	NE - None
410 - 410nm	PM - PM Panda Fiber,	9 - 900um Loose Tube	10 - 1.0m	FA - FC/APC
420 - 420nm	Slow Axis Aligned to Port 1	2 - 2.0mm Loose Tube	15 - 1.5m	FU - FC/UPC
430 - 430nm	P4 - PM Panda Fiber,	3 - 3.0mm Loose Tube	20 - 2.0m	SA - SC/APC
440 - 440nm	Slow Axis 45° Aligned to Port 1		SS - Specify	SU - SU/APC
450 - 450nm				LA - LC/APC
458 - 458nm				LU - LC/UPC
SSS - Specify				SS - Specify