

520nm PM Manual Variable Optical Attenuator

520nm PM Manual Variable Optical Attenuator is a fiber component which can control the attenuation of the optical power by adjusting the screw manually, the attenuation value can be up to 60dB, it's widely used in Quantum Communication field, Optical Power Testing System, higher power version is available.

Application:

Quantum Communication
Fiber Laser
Testing System
Lab And Research

Features:

Low Original Loss
High Return Loss
High Attenuation Range
High Reliability




Specification:

Parameter	Symbol	Value	Unit
Center Wavelength	λ	520	nm
Bandwidth	BW	± 10	nm
Attenuation Range		1.0-60	dB
Max. Original Loss	IL	1.0	dB
Adjustment Precision		0.02	dB
Min. Extinction Ratio	ER	18	dB
Min. Return Loss	RL	50	dB
Max. Optical Power (CW)	P	500	mW
Max. Tensile Load		5	N
Fiber Type		PM460-HP Panda fiber	-
Operating Temperature	T	-5~70	°C
Storage Temperature	T	-40~85	°C
Package Dimension		26x18x8	mm

Notice: Above specifications are tested at center wavelength without connector in room temperature @23°C.

For devices with connectors, IL will be 0.3dB higher, ER will be 2dB lower, RL will be 5dB lower, slow axis is default aligned to the connector key.

Drawing:



Ordering Information (Part Number):

PMVOA- WWW - J - LL - CC			
WWW	J	LL	CC
Wavelength	Fiber Jacket	Fiber Length	Connector
505 - 505nm	B - 250um Bare Fiber	05 - 0.5m	NE - None
509 - 509nm	9 - 900um Loose Tube	10 - 1.0m	FA - FC/APC
520 - 520nm	2 - 2.0mm Loose Tube	15 - 1.5m	FU - FC/UPC
532 - 532nm	3 - 3.0mm Loose Tube	20 - 2.0m	SA - SC/APC
556 - 556nm		SS - Specify	SU - SU/APC
560 - 560nm			LA - LC/APC
570 - 570nm			LU - LC/UPC
582 - 582nm			SS - Specify
SSS - Specify			