

780nm SM Manual Variable Optical Attenuator

780nm SM Manual Variable Optical Attenuator is a fiber component which can control the attenuation of the optical power by adjusting the screw, the attenuation value can be up to 60dB, it's widely used in Quantum Communication field, Optical Power Testing System, higher power version is available.

Application:

Quantum Communication
Fiber Laser
Testing System
Lab And Research

Features:

Low Original Loss
High Return Loss
High Attenuation Range
High Reliability




Specification:

Parameter	Symbol	Value	Unit
Center Wavelength	λ	780	nm
Bandwidth	BW	± 20	nm
Attenuation Range		0.8-60	dB
Max. Original Loss	IL	0.8	dB
Adjustment Precision		0.02	dB
Max. Polarization Dependent Loss	PDL	0.15	dB
Min. Return Loss	RL	50	dB
Max. Optical Power (CW)	P	500	mW
Max. Tensile Load		5	N
Fiber Type		HI 780 fiber	-
Operating Temperature	T	-5~70	°C
Storage Temperature	T	-40~85	°C
Package Dimension		26x18x8	mm

Notice: Above specifications are tested at center wavelength without connector in room temperature @23°C.

For devices with connectors, IL will be 0.3dB higher, RL will be 5dB lower.

Drawing:



Ordering Information (Part Number):

SMVOA- WWW - J - LL - CC			
WWW	J	LL	CC
Wavelength	Fiber Jacket	Fiber Length	Connector
760 - 760nm	B - 250um Bare Fiber	05 - 0.5m	NE - None
780 - 780nm	9 - 900um Loose Tube	10 - 1.0m	FA - FC/APC
785 - 785nm	2 - 2.0mm Loose Tube	15 - 1.5m	FU - FC/UPC
790 - 790nm	3 - 3.0mm Loose Tube	20 - 2.0m	SA - SC/APC
793 - 793nm		SS - Specify	SU - SU/APC
795 - 795nm			LA - LC/APC
SSS - Specify			LU - LC/UPC
			SS - Specify